Pipet Tip Compatibility Chart

for HTL Pipettors

HTL LAB SOLUTIONS

NOTE: HTL pipettors are calibrated using non-filtered tips, thus pipettor recalibration might be required when using filter tips.

				HTL Discovey Comfort, Labmate Pro, and Optipette													HTL Discovery Pro										HTL Clinipet+																	
			Channels	Single-channel										Multi-channel					Single-channel						Multi-channel				Single-channel																
	Pipet Tip	Cat. No.	Volume Range	0.1-2 µL	0.5-10 µL	2-20 µL	5 - 50 µL	10-100 µL	20-200 µL	50 - 250 µL	100-1000 µL	1000-5000 µL	1000-10000 µL	0.5-10 µL	5-50 µL	20-200 µL	50-300 µL	0.1-2 µL	0.5-10 µL	2-20 µL	10-100 µL	20-200 µL	100-1000 µL	0.5-10 µL	5-50 µL	20-200 µL	50-300 µL	5 µL	10 µL	20 µL	25 µL	30 µL	50 µL	75 µL	100 µL	150 µL	200 µL	220 µL	250 µL	300 µL	500 µL	750 µL	1,000 µL
Corning®	DeckWorks	4125	0.1-10 µL		•									•					•					•																			
		4135			•									•					•					•																			
		4136	1-20 µL			•														•																							
		4137	1-100 µL				•	•														•																					
		4126	1-200 µL			•		•	•						•	•					•	•	•			•	•		•	•	•	•	•	•	•	•	•						
		4138							•							•							•																				
		4139							•							•							•																				
		4128	1-300 µL						•	•						•	•						•				•																
		4129	100-1000 µL								•												•															•	•	•	•	•	•
		4140									•												•																				
	Isotip	4801	0.1-2 µL	•														•																									
		4807	0.2-10 µL	•	•									•				•	•					•																			
		4808	0.5-10 µL		•									•					•					•																			
		4821	1-30 µL			•														•																							
		4823	1-200 µL						•							•					•																						
		4809	100-1000 µL								•												•																				
Axygen®	MultiRack	MR-10XT*	0.1-10 µL		•									•					•					•																			
		MRF-10XT*			•									•					•					•																			
		MRF-20	1-20 µL			•														•																							
		MRF-100	1-100 µL				•	•														•																					
		MR-200	1-200 µL					•	•						•							•	•			•		•	•	•	•	•	•	•	•	•						
		MRF- 200XT*						•	•						•							•	•			•																
		MRF-200NX							•						•							•	•			•																
		MRF- 300XT*	1-300 µL						•						•	•						•	•			•	•															
		MR-300XT*							•						•	•						•	•			•	•															
		MR-300							•						•	•						•	•			•	•															
		MR-1000XT*	50 - 1250 µL							•													•															•	•	•	•	•	•
		MRF-1000XT*								•													•																				
	Universal Fit	T-300	0.5-10 µL	•	•									•					•					•																			
		TF-300		•	•									•					•					•																			
		TXL-10			•									•										•																			
		TF-20	0.5-20 µL			•														•																							
		TF-50	0.5-50 µL				•						•													•																	
		TF-100	1-100 µL					•														•																					
		TR-222	1-200 µL					•	•						•							•	•			•	•		•	•	•	•	•	•	•	•	•						
		TF-200							•						•							•	•			•	•															
		T-350	1-300 µL						•	•					•	•						•	•			•	•															
		TF-350							•	•					•	•						•	•			•	•															
		T-1000	100-1000 µL								•												•															•	•	•	•	•	•
		TF-1000									•												•															•	•	•	•	•	•
		TF-1200	100-1100 µL								•												•																				
		T-5000	1-5 mL									•																															
		T-10ML	1-10 mL										•																														
Labnet	BioFree™	P1000-10	0.5-10 µL	•	•									•					•					•																			
		P1000-200	1-200 µL			•	•	•	•						•	•					•	•	•			•	•		•	•	•	•	•	•	•	•	•						
		P1000-300	1-300 µL							•							•										•																
		P1000-1000	100-1000 µL								•												•															•	•	•	•	•	•
		P3998	1-5 mL									•																															
		K943	1-10 mL										•																														
Eppendorf	epT.I.P.S.®	–	2-200 µL					•	•											•	•	•				•																
			20-300 µL																								•																
			50-1000 µL								•												•																				
Gilson	Diamond®	–	0.1-10 µL		•														•					•																			
			0.1-20 µL																	•																							
			2-200 µL					•	•													•	•				•																
			20-300 µL																								•																
			100-1000 µL								•												•															•	•	•	•	•	•
			1-5 mL									•																															
BrandTech	Standard	–	0.1-20 µL			•														•																							
			5-300 µL																								•																
			50-1000 µL								•												•															•	•	•	•	•	•
Sartorius	Optifit®	–	0.1-10 µL		•														•					•																			
			0.5-200 µL					•	•											•	•	•				•																
			5-350 µL																								•																
			10-1000 µL								•												•															•	•	•	•	•	•
Starlab	TipOne®	–	0.1-10 µL		•														•					•																			
			1-200 µL			•		•	•						•						•	•	•			•																
			1-300 µL																								•																
			100-1000 µL																								•																
ThermoFisher	Finntip®	–	5-200 µL					•	•						•							•	•			•																
			5-300 µL													•											•																
			100-1000 µL								•												•															•	•	•	•	•	•

*Extended length tip

HTL LAB SOLUTIONS

Corning HTL SA
Daniszewska 4
03-230 Warsaw, Poland
t. +48 22 492 19 00
f. +48 22 492 19 93
htlcs@corning.com
www.htl.com.pl

ASIA/PACIFIC
Australia/New Zealand
t 61 427286832
Chinese Mainland
t 86 21 3338 4338
India
t 91 124 4604000
Japan
t 81 3-3586 1996
Korea
t 82 2-796-9500
Singapore
t 65 6572-9740
Taiwan
t 886 2-2716-0338

EUROPE
HTL.sales@corning.com
HTL.service@corning.com

LATIN AMERICA
grupoLA@corning.com
Brazil
t 55 (11) 3089-7400
Mexico
t (52-81) 8158-8400

Warranty/Disclaimer: Unless otherwise specified, all products are for research use or general laboratory use only.* Not intended for use in diagnostic or therapeutic procedures. Not for use in humans. These products are not intended to mitigate the presence of microorganisms on surfaces or in the environment, where such organisms can be deleterious to humans or the environment. Corning Life Sciences makes no claims regarding the performance of these products for clinical or diagnostic applications. *For a listing of US medical devices, regulatory classifications or specific information on claims, visit www.corning.com/resources.

For a listing of trademarks, visit www.corning.com/clstrademarks. All other trademarks are the property of their respective owners.
© 2023 Corning Incorporated. All rights reserved. 5/23 CLSHTL-EQ-010